

FIG. 3




FIG. 4

SYMBOLS	5B	4B
0	1 1 1 1 0	0 0 0 0
1	01001	0 0 0 1
2	10100	0 0 1 0
3	10101	0 0 1 1
	01010	0100
4	0 1 0 1 1	0 1 0 1
5	0 1 1 1 0	0 1 1 0
6	0 1 1 1 1	0111
7	1 0 0 1 0	1000
8	10011	1001
9	10110	1010
A	10111	1011
В	11010	1100
C	1 1 0 1 1	1101
D	11100	1110
Е	11101	1111
F F	11111	1010
1 (IDLE)		0 0 0 1
H(HALT)		1 1 0 1
JK (STARTING		
DELIMITER)		0 1 0 1
T (ENDING	0 1 1 0 1	
DELIMITER)		0 1 1 0
R(RESET)	00111	0 1 1 1
S(SET)	1 1 0 0 1	0 0 1 0
Q(QUIET)	0 0 0 0 0	0 0 1 0
V(VIOLATION)	0 0 0 0 1	0 0 1 0
V	0 0 0 1 0	0 0 1 0
V	0 0 0 1 1	0 0 1 0
L(EMBEDDED DELIMITER)	0 0 1 0 1	0 0 1 0
V	0 0 1 1 0	0 0 1 0
V	0 1 0 0 0	0 0 1 0
V	0 1 1 0 0	0 0 1 0
V	10000	0010

FIG. 5A

				HIGH
T	p	Α		LOW
Тр	Δ	*	HIGH	
	۲	71		LOW

FIG. 5B

				
IN	CASE OF ON		XXXXXXXXXX	X:SYMBOL DIFFERENT FROM Q
IN	CASE OF OFF	:	→ QQQQQQQQQQ	

FIG. 6




FIG. 7




FIG. 8

